


Overview

The GCS-601 series electronic locks adopt a fully-body design with an elegant appearance combined with superior lock performance.

The lock is suitable for small to very large scale hotels and easily to replace existing mechanical or electronic door locks throughout a facility which makes it very popular in the market.



FEATURES

Standalone electronic lock with RFID technology.

Supports Mobile Access.

High security mortise lockcase with ANSI standard.

CE, FCC approved.

Solid steel handles with self-lubricating long life bearings.

3-point steel latch construction with an anti-friction mechanism.

Panic release function – the deadbolt and latch are automatically retracted by inside handle for easy regress in emergency situations.

Long lasting Escutcheon and durable handle levers.

Lock programming and audit records are not erased during battery replacement.

Powered by four (4) AA batteries that provide up to 12-18 months normal life.

Up to 990 event audit trail.

Low battery indicator alerts staff.

High security concealed cylinder override.

Customize key cards for different levels of access authorization.

Opening error detected by LED light and beep sound.

All cards have an effective period. Guest cards have limited access functions and expiration date.


Handle
Options



1#Stainless Steel



2# Zinc Alloy



3# Zinc Alloy



5#Stainless Steel



6#Stainless Steel

Material

Escutcheon and Handles(Stainless steel quality SUS304)
RFID and Battery Cover:Polycarbonate UL94V0 (Makrolon 6555)

Metal finishes

Brush Stainless Steel (Stainless Steel with PVD)
Satin Brass (Stainless Steel with PVD)
Black Nickel (Stainless Steel with PVD)

Battery location

Inside of the room

Power

6V DC 4 × AA alkaline batteries

Low Battery Indicator

Alerts staff that batteries need to be changed soon

Emergency Opening Option

Mechanical metal Key

User interface

2 colored LED display (blue and red)

Locking mechanism

Electro-mechanical locking mechanism located in the lockcase.

Working Temperature

-25°C-60°C

Working Humidity

10%-85%

Audit Trail

990 latest records include mechanical key

Door Thickness

40-70mm

Certifications

China Ministry of Public Security (MA) European CE-RED Directives
USA FCC Part 15C (FCC ID) Australia C-Tick AS/NZS 4268

